

CABLE PROTECTION HOSE FOR MINING & INDUSTRY FRAS - FIRE RESISTANT ANTI STATIC

AS 1802 AS 2660



NSW dept. of mineral resources approved

Tube: Black conductive SBR/NR
Reinforcement: High tensile textile cords
Cover: Black conductive SBR - abrasion, ozone and fire resistant
Use: Cable protection in underground mines.
 Also suitable for light duty air and water delivery max 5 bar (75 psi)
Safety factor: 3:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)
Length: 61m Rolls

↔		↔		⚡		⤴		%		⚖	
mm	inch	mm	inch	bar	psi	mm	inch		kg/m	lb/ft	
13	1/2	21	0,83	5	75				0,250	0,170	
16	5/8	24	0,94	5	75				0,290	0,195	
19	3/4	29	1,14	5	75				0,420	0,280	
25	1	35	1,38	5	75				0,520	0,350	
32	1 1/4	42	1,65	5	75				0,650	0,440	
38	1 1/2	48	1,89	5	75				0,750	0,500	
45	1 3/4	55	2,17	5	75				0,870	0,580	
51	2	61	2,40	5	75				0,980	0,660	

NA	LA	NEU	CEU	SA	AP	AU
----	----	-----	-----	----	----	----



HUNTER ENGINEERING SALES
 29 Torrens Avenue, Cardiff NSW 2285
 PO Box 546, Warners Bay NSW 2282
Phone 02 49528533 Fax 02 49529117
 Email info@hesales.com.au