

Termco Heat Shrink

Termco Thin Wall Heat Shrink Rolls



- Cross linked polyolefin
- Flame retardant (clear heatshrink is not flame retardant)
- Shrink ratio 2:1
- Operating temp.: -55 to +125°C (Clear: -55 to +105°C)



Heat Shrink Colour Key

Blue (BL)	Yellow (Y)	White (W)
Green (G)	Clear (CL)	Green/Yellow(GY)
Black (BK)	Red (R)	

Stock code example: HS013BK

Part Number	Available Colours	Inside Diameter (mm)	Inside Diameter After Full Shrink (mm)	Wall Thickness After Full Shrink (mm)	Roll Size
HS001.5(Colour abbreviation)	BL, Y, G, CL, BK, R, W, GY	1.5	0.75	0.36	200m
HS002.5(Colour abbreviation)	BL, Y, G, CL, BK, R, W, GY	2.5	1.25	0.44	200m
HS003.5(Colour abbreviation)	BL, Y, G, CL, BK, R, W, GY	3.5	1.75	0.44	200m
HS005(Colour abbreviation)	BL, Y, G, CL, BK, R, W, GY	5.0	2.50	0.56	100m
HS007(Colour abbreviation)	BL, G, CL, BK, R, W, GY	7.0	3.50	0.56	50m
HS010(Colour abbreviation)	BL, G, CL, BK, R, W, GY	10.0	5.0	0.56	50m
HS013(Colour abbreviation)	BL, G, CL, BK, R, W, GY	13.0	6.5	0.65	50m
HS016(Colour abbreviation)	BL, G, CL, BK, R, W, GY	16.0	8.0	0.69	50m
HS020(Colour abbreviation)	BL, G, CL, BK, R, W, GY	20.0	10.0	0.80	50m
HS025(Colour abbreviation)	BL, G, CL, BK, R, W, GY	25.0	12.5	0.8	50m
HS030(Colour abbreviation)	BL, G, CL, BK, R, W, GY	30.0	15.0	0.9	50m
HS040(Colour abbreviation)	BL, G, CL, BK, R, W, GY	40.0	20.0	1.0	25m
HS050(Colour abbreviation)	BL, G, CL, BK, R, W, GY	50.0	25.0	1.0	25m
HS076(Colour abbreviation)	BL, G, CL, BK, R, W, GY	76.0	38.0	1.15	25m
HS100(Colour abbreviation)	BL, G, CL, BK, R, W	100.0	50.0	1.3	25m
HS125(Colour abbreviation)	BL, G, CL, BK, R, W	125.0	63.5	1.3	15m

Termco Thin Wall Heat Shrink Lengths



- 1.2m lengths
- Cross linked polyolefin
- Flame retardant (clear heat shrink is not flame retardant)
- Shrink ratio 2:1
- Operating temp.: -55 to +125°C (Clear: -55 to +105°C)



Heat Shrink Colour Key

Blue (BL)	Yellow (Y)	White (W)
Green (G)	Clear (CL)	Green/Yellow(GY)
Black (BK)	Red (R)	

Stock code example: HSC020R

Part Number	Available Colours	Inside Diameter (mm)	Inside Diameter After Full Shrink (mm)	Wall Thickness After Full Shrink (mm)
HSC001.5(Colour abbreviation)	BL, Y, G, CL, BK, R, W, GY	1.5	0.75	0.36
HSC002.5(Colour abbreviation)	BL, Y, G, CL, BK, R, W, GY	2.5	1.25	0.44
HSC003.5(Colour abbreviation)	BL, Y, G, CL, BK, R, W, GY	3.5	1.75	0.44
HSC005(Colour abbreviation)	BL, Y, G, CL, BK, R, W, GY	5.0	2.50	0.56
HSC007(Colour abbreviation)	BL, G, CL, BK, R, W, GY	7.0	3.50	0.56
HSC010(Colour abbreviation)	BL, G, CL, BK, R, W, GY	10.0	5.0	0.56
HSC013(Colour abbreviation)	BL, G, CL, BK, R, W, GY	13.0	6.5	0.65
HSC020(Colour abbreviation)	BL, G, CL, BK, R, W, GY	20.0	10.0	0.80
HSC025(Colour abbreviation)	BL, G, CL, BK, R, W, GY	25.0	12.5	0.8
HSC040(Colour abbreviation)	BL, G, CL, BK, R, W, GY	40.0	20.0	1.0
HSC050(Colour abbreviation)	BL, G, CL, BK, R, W, GY	50.0	25.0	1.0
HSC076(Colour abbreviation)	BL, G, CL, BK, R, W, GY	76.0	38.0	1.15
HSC100(Colour abbreviation)	BL, G, CL, BK, R, W	100.0	50.0	1.3

Termco Heat Shrink

Termco Dual Wall Heat Shrink

- Cross linked adhesive lined polyolefin
- Flame retardant
- Shrink ratio 3:1
- Operating temp.: -55 to +125°C
- Bonds perfectly to various wire jackets



Part Number	Colour	Inside Diameter (mm)	Inside Diameter After Full Shrink (mm)	Wall Thickness After Full Shrink (mm)		Length	Spool
				w1	w2		
DWL3/1	Black	3.0	1.0	1.0	0.5	1.2m	200m
DWL3/1R	Red						
DWL5/1.6	Black	5.0	1.6	1.0	0.5	1.2m	100m
DWL5/1.6R	Red						
DWL6/2	Black	6.0	2.0	1.0	0.5	1.2m	50m
DWL6/2R	Red						
DWL9/3	Black	9.0	3.0	1.4	0.6	1.2m	50m
DWL9/3R	Red						
DWL12/4	Black	12.0	4.0	1.6	0.8	1.2m	25m
DWL12/4R	Red						
DWL18/6	Black	18.0	6.0	2.15	0.8	1.2m	25m
DWL18/6R	Red						
DWL24/8	Black	24.0	8.0	2.4	1.0	1.2m	25m
DWL24/8R	Red						
DWL40/13	Black	40.0	13.0	2.4	1.0	1.2m	25m
DWL39/13R	Red	39.0	13.0	2.4	1.0	1.2m	25m



Termco Medium Wall Heat Shrink

- Cross linked adhesive lined polyolefin
- Flame retardant
- Shrink ratio 3:1
- Operating temp.: -55 to +110°C
- UV resistant



Part Number	Colour	Inside Diameter (mm)	Inside Diameter After Full Shrink (mm)	Wall Thickness After Full Shrink (mm)	Length
MWL012/3	Black	12.0	3.0	1.5	1.2m
MWL016/5	Black	16.0	5.0	1.5	1.2m
MWL022/06	Black	22.0	6.0	2.0	1.2m
MWL033/08	Black	33.0	8.0	2.0	1.2m
MWL040/12	Black	40.0	12.0	2.0	1.2m
MWL055/16	Black	55.0	16.0	2.0	1.2m
MWL065/19	Black	65.0	19.0	2.5	1.2m
MWL075/22	Black	75.0	22.0	2.7	1.2m
MWL095/25	Black	95.0	25.0	2.9	1.2m
MWL115/34	Black	115.0	34.0	3.2	1.2m
MWL140/42	Black	140	42	3.5	1.2m

Termco Heat Shrinkable Cable Repair Sleeve

- Shrinkable wrap around sleeve
- UV & weather resistant
- Provides excellent corrosion and abrasion protection
- Operating temp.: -40° to + 65°C



Part Number	Inside Diameter (mm)	Wall Thickness Before Shrink (mm)	Inside Diameter After Full Shrink (mm)	Wall Thickness After Full Shrink (mm)	Length
HSWAS036010	38	1.5	9	2.4	1.0m
HSWAS055013	57	1.5	13	2.5	1.0m
HSWAS085020	85	1.5	20	3.0	1.0m
HSWAS108027	110	1.5	27	3.0	1.0m
HSWAS136030	138	1.5	30	3.2	1.0m

Termco & Raychem Heat Shrink

Termco & Raychem Heat Shrink

Termco Heat Shrink End Cap

- Cross linked adhesive lined polyolefin
- Excellent sealing properties
- Shrink ratio 3:1
- Operating temp.: -55 to +110°C
- UV resistant



Part Number	Inside Diameter (mm)	End Cap Length (mm)	Inside Diameter After Full Shrink (mm)	Wall Thickness After Full Shrink (mm)
HSEC048015	4.8	30	1.5	1.1
HSEC0602	6.0	30	2.0	1.2
HSEC0903	9.0	35	3.0	1.3
HSEC1204	12.0	40	4.0	2.6
HSEC1405/55	14.0	45	5.0	2.2
HSEC2006	20.0	55	6.0	2.8
HSEC25085	25.0	68	8.5	2.8
HSEC3516	35.0	83	16.0	3.3
HSEC4015	40.0	90	15.0	3.3
HSEC5516	55.0	103	16.0	3.5
HSEC7536	75.0	120	36.0	4.0
HSEC10052	100.0	140	52.0	4.0
HSEC14560	145.0	150	60.0	4.0



Termco Heat Shrink Stand

Available on request, please contact sales@engsup.com.au or call us on 08 9258 8444
Heatshrink sold separately



Raychem MWTM Medium Wall Heat Shrink



- Cross linked adhesive lined polyolefin
- Flame retardant
- Shrink ratio 3:1
- UV resistant



Part Number	Inside Diameter (mm)	Inside Diameter After Full Shrink (mm)	Wall Thickness Before & After Full Shrink (mm)		Length	Spool Without Sealant
			w1	w2		
MWTM10/3-1200	10.0	3.0	0.3	1.0	1.2m	40m
MWTM16/5-1200	16.0	5.0	0.3	1.4	1.2m	40m
MWTM25/8-1200	25.0	8.0	0.4	2.0	1.2m	40m
MWTM35/12-1200	35.0	12.0	0.4	2.0	1.2m	30m
MWTM50/16-1200	50.0	16.0	0.5	2.0	1.2m	25m
MWTM63/19-1200	63.0	19.0	0.6	2.4	1.2m	15m
MWTM75/22-1200	75.0	22.0	0.6	2.7	1.2m	-
MWTM85/25-1200	85.0	25.0	0.6	2.8	1.2m	-
MWTM95/29-1200	95.0	29.0	0.7	3.1	1.2m	-
MWTM115/34-1200	115.0	34.0	0.7	3.1	1.2m	-
MWTM140/42-1200	140.0	42.0	0.7	3.1	1.2m	-
MWTM160/50-1200	160.0	50.0	0.7	3.2	1.2m	-
MWTM180/60-1200	180.0	60.0	0.7	3.2	1.2m	-

Raychem WCSM Heavy-wall Heat Shrink



- Cross linked adhesive lined polyolefin
- Flame retardant
- Shrink ratio 3:1
- UV resistant



Part Number	Inside Diameter (mm)	Inside Diameter After Full Shrink (mm)	Wall Thickness Before & After Full Shrink (mm)		Length
			w1	w2	
WCSM16/4-1200	16.0	4.0	0.9	2.4	1.2m
WCSM24/6-1200	24.0	6.0	1.0	2.7	1.2m
WCSM34/8-1200	34.0	8.0	1.3	4.0	1.2m
WCSM48/12-1200	48.0	12.0	1.5	4.5	1.2m
WCSM56/16-1200	56.0	16.0	1.5	4.4	1.2m
WCSM70/20-1200	70.0	20.0	1.4	4.4	1.2m
WCSM90/25-1200	90.0	25.0	1.3	4.3	1.2m
WCSM110/30-1200	110.0	30.0	1.2	4.3	1.2m
WCSM130/35-1200	130.0	35.0	1.2	4.3	1.2m
WCSM160/50-1200	160.0	50.0	1.0	4.3	1.2m
WCSM180/50-1200	180.0	50.0	1.0	4.3	1.2m